

Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Gear Protection Spray

· Article number: LOS 280

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Lubricant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EURO-LOCK Vertriebs-GmbH

Nordweststrasse 3 D-59387 Ascheberg

Tel.: +49 (0) 2593/95887 - 0 Fax.: +49 (0) 2593/95887 - 29

www.euro-lock.de

· Further information obtainable from:

Tel.: +49 (0) 2593/95887 - 0 E-Mail: info@euro-lock.de

1.4 Emergency telephone number:

Tel: +49 (0) 2593/95887 - 0 Monday - Thursday 8:00 - 17:00 CET, Friday 8:00 - 13:00 CET

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes pentane

Hydrocarbons, C5-C7, n-alkanes, isoalkanes, <5% n-hexane

Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, <5% n-hexane

(Contd. on page 2)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

(Contd. of page 1)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing vapours or spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P391 Collect spillage.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- P501 Dispose of contents/container to hazardous or special waste collection point.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 920-750-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cycloalkanes Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	10-20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30-xxxx	pentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-10%
EC number: 922-114-8	Hydrocarbons, C5-C7, n-alkanes, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	2.5-10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
EC number: 926-605-8 Reg.nr.: 01-2119486291-36-xxxx	Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-10%

GB -



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

	(Cor	ntd. of page 2)
CAS: 67-56-1	methanol	1.0-2.5%
EINECS: 200-659-6	Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370	
EC number: 918-668-5	Hydrocarbons, C9, aromatics	0.1-1.0%
Reg.nr.: 01-2119455851-35-xxxx	 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336 	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

 \cdot 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

• 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

(Contd. of page 3)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) Industrial Processing.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingre	dients with limit values that require monitoring at the workplace:
CAS:	109-66-0 pentane
WEL	Long-term value: 1800 mg/m³, 600 ppm
CAS:	106-97-8 butane
	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
CAS:	67-56-1 methanol
	Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk

- \cdot ${\bf Additional}$ information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- \cdot General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Not necessary if room is well-ventilated.
- · Recommended filter device for short term use: Filter AX
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

(Contd. of page 4)

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.7 mm

· Penetration time of glove material

≥240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on b	asic physical a	and chemical	properties
------------------------	-----------------	--------------	------------

· General Information

· Appearance:

Form: Aerosol
Colour: Black

Odour: Solvent-like
Odour threshold: Not determined.

· pH-value:

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

Flash point: Not applicable, as aerosol.
 Flammability (solid, gas): Not applicable.

· Ignition temperature: >200 °C

• **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Not determined.

• Explosive properties: Product is not explosive. However, formation of explosive air/

Not applicable.

Not determined.

vapour mixtures are possible.

 \cdot Explosion limits:

· Evaporation rate

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

Density at 20 °C: 0.80535 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 6)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

(Contd. of page 5)

Kinematic: Not determined.

Organic solvents: 57.0 % **VOC** (**EC**) 569.7 g/l

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:	
ATE (Acute Toxicity Estimates)	
Inhalative I C50// h >36.0 mg/l	

Inhalative LC50/4 h >36.9 mg/l

CAS: 07-50-1 methanol		
Oral	LD50	100 mg/kg (ATE)
		300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eve damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

(Contd. of page 6)

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Generally not hazardous for water

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
15 01 04	metallic packaging
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR/RID/ADN	UN1950 AEROSOLS, ENVIRONMENTALLY
	HAZARDOUS
IMDG	AEROSOLS, MARINE POLLUTANT
IATA	AEROSOLS, flammable

· ADR/RID/ADN



· Class
 · Label
 2 5F Gases.
 2.1

· IMDG



· Class 2.1

(Contd. on page 8)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

	(Contd. of page
Label	2.1
· IATA	
Class Label	2.1 2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant: Special marking (ADR/RID/ADN):	Ja Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code Segregation Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
· Tunnel restriction code	D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $150\ t$

(Contd. on page 9)



Printing date 06.06.2018 Version number 16 Revision: 06.06.2018

Trade name: Gear Protection Spray Article-No.: LOS 280

(Contd. of page 8)

- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\;t$
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40, 69
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product Safety department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

 $A quatic\ Chronic\ 2: Hazardous\ to\ the\ aquatic\ environment\ -\ long-term\ aquatic\ hazard\ -\ Category\ 2$

* Data compared to the previous version altered.

GB