

EURO-LOCK

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2018

Version number 78

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision: 09.05.2018

· 1.1 Product identifier · Trade name: Kriechö Article number: LOS60 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Lubricant · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Euro-Lock Vertriebs-GmbH Nordweststr. 3 D - 59387 Ascheberg Tel.: +49 (0) 2593/95887-0 Tel.: +49 (0) 2593/95887-29 www.euro-lock.de info@euro-lock.de Further information obtainable from: Tel.: +49 (0) 2593/95887-0 info@euro-lock.de **1.4 Emergency telephone number:** Tel.: +49 (0) 2593/95887-0 Monday - Thursday 8.00 a.m. - 5.00 p.m. and Friday 8.00 a.m. - 1.00 p.m. **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 · Signal word Danger · Hazard-determining components of labelling: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Distillates (petroleum), hydrotreated light naphthenic · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. P211 Do not pierce or burn, even after use. P251 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Dispose of contents/container to hazardous or special waste collection point. P501 · Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation. (Contd. on page 2) GB



Page 2/9

Printing date 30.05.2018

Version number 78

Revision: 09.05.2018

```
Trade name: Kriechð
```

Article number: LOS60

(Contd. of page 1)

· 2.3 Other hazards

 \cdot Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	25-<50%
6	🚯 Asp. Tox. 1, H304	
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 64742-53-6 EINECS: 265-156-6 Reg.nr.: 01-2119480375-34-xxxx	Distillates (petroleum), hydrotreated light naphthenic	10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<5%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx	 2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 	1-<2.5%
· Regulation (EC) No 648/2004 on	detergents / Labelling for contents	
aliphatic hydrocarbons		≥30%
aromatic hydrocarbons		<5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- Take affected persons into fresh air and keep quiet.
- · After skin contact:
- Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

GB -

Printing date 30.05.2018

EURO-LOCK

Version number 78

Trade name: Kriechö

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Article number: LOS60

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Foam

Fire-extinguishing powder

- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

- Can form explosive gas-air mixtures.
- Formation of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information
- Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Mount respiratory protective device.

Keep away from ignition sources.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) Industrial processing

(Contd. on page 4)





Version number 78

Revision: 09.05.2018

Trade name: Kriechö

×

Printing date 30.05.2018

EURO-LOCK

Article number: LOS60

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

-	dients with limit values that require monitoring at the workplace:
CAS:	106-97-8 butane
	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)
	111-76-2 2-butoxyethanol
WEL	Short-term value: 246 mg/m ³ , 50 ppm
	Long-term value: 123 mg/m ³ , 25 ppm
	Sk, BMGV
Ingre	dients with biological limit values:
CAS:	111-76-2 2-butoxyethanol
BMG	V 240 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: butoxyacetic acid
Addit	ional information: The lists valid during the making were used as basis.
8.2 Ex	xposure controls
	nal protective equipment:
	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing
	hands before breaks and at the end of work.
	t inhale gases / fumes / aerosols.
	contact with the eyes and skin.
	ratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
	nmended filter device for short term use: Filter AX
Prote	ction of hands:
The gl	love material has to be impermeable and resistant to the product/ the substance/ the preparation.
· Mater	rial of gloves
The se	election of the suitable gloves does not only depend on the material, but also on further marks of qua
and va	aries from manufacturer to manufacturer.
Fluore	ocarbon rubber (Viton)
(EN 3	74)
Recon	nmended thickness of the material: ≥ 0.45 mm
· Penet	ration time of glove material
The ex	xact break trough time has to be found out by the manufacturer of the protective gloves and has to
observ	ved.
≥240 1	min
· Eye p	rotection:
	Tightly sealed goggles
(EN 1	
	protection:
Protec	tive work clothing
	(Contd. on pag



Printing date 30.05.2018

Version number 78

Revision: 09.05.2018

(Contd. of page 4)

Trade name: Kriechð

Article number: LOS60

(EN 13034-6)

×

SECTION 9: Physical and chemical properties			
• 9.1 Information on basic physical and chemical properties			
· General Information			
· Appearance: Form:	Aerosol		
Colour:	Colourless		
· Odour:	Petroleum-like		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/freezing point:	Undetermined.		
Initial boiling point and boiling range			
· Flash point:	Not applicable, as aerosol.		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	>200 °C		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Not determined.		
· Explosive properties:	Not determined.		
· Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
· Vapour pressure:	Not determined.		
· Density at 20 °C:	0.69181 g/cm ³		
· Relative density	Not determined.		
· Vapour density	Not determined.		
· Evaporation rate	Not applicable.		
· Solubility in / Miscibility with			
water:	Not miscible or difficult to mix.		
· Partition coefficient: n-octanol/water:	Not determined.		
· Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Organic solvents: VOC (EC)	85.6 % 591.9 g/l		
Solids content:	0.0 %		
· 9.2 Other information	No further relevant information available.		

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

[—] GB

Printing date 30.05.2018

Revision: 09.05.2018

Trade name: Kriechð

Article number: LOS60

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	77,321 mg/kg (rat)
Dermal	LD50	20,898 mg/kg (rab)
Inhalative	LC50/4 h	575 mg/l
CAS: 111-76-2 2-butoxyethanol		
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)
	LC50/4 h	11 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eve damage/irritation Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)



Version number 78



Vancia

Printing date 30.05.2018

Version number 78

Revision: 09.05.2018

Trade name: Kriechð

Article number: LOS60

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

×

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	
· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1950
 14.2 UN proper shipping name ADR/RID/ADN IMDG IATA 	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
• 14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler): EMS Number:	- F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	 SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriate



Printing date 30.05.2018

Version number 78

Revision: 09.05.2018

Trade name: Kriechö

Article number: LOS60

	(Contd. of page 2
	subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to A	Annex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR/RID/ADN	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- · Department issuing SDS: Product Safety department.
- · Contact: info@euro-lock.de
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)

GB



Printing date 30.05.2018

Version number 78

Revision: 09.05.2018

Trade name: Kriechð

Article number: LOS60

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent	(Contd. of page 8)
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
• * Data compared to the previous version altered.	
	GB

